

Product sheet

Paralel

armchair polished aluminium base

Technical Data

- Backrest - moulded foam, density of 75 kg/m³, upholstered;
 - Seat - moulded foam, density of 98 kg/m³, upholstered;
 - Armrests (option with extra charge) – wood, natural beech, colour: black;
 - Base PR1PP19/PR2PP19 - 4-star, polished aluminium, swivel seat - 360°, aluminium cast, legs finished with polypropylene feet;
 - Base PR1PP19K/PR2PP19K - 4-star, polished aluminium, swivel seat - 360°, aluminium cast, castors for soft floors, option with extra charge - castors for hard floors;
 - Max. load 120 kg
-

Selected configuration

PR2PP19

Height: 960 mm

Width: 670 mm

Length: 670 mm

Paralel: High backrest

Colour of the frame: Polished aluminum

Colour of the seat: M-62054 Mustard

Armrest: No armrests

Sustainability

- Sustainable production – we are not indifferent to the environmental impact of our furniture, therefore we provide the essential information on the lifecycle of Paralel seating via the Environmental Product Declaration (EPD).
 - Aluminium bases are powder-coated to reduce the emission of Volatile Organic Compounds.
 - Aluminum used in the production of the Paralel base is easily recyclable.
 - Some of the available upholstery fabrics are made from recycled materials.
-



Guarantee

.mdd products - 5 years.

Electrical components - 2 years.

Assembly manuals



Certificates



Material composition

- MFC: 6%
- Steel: 46%
- Plastic: 10%
- Fabric: 6%
- Cardboard: 15%
- Polyurethane foam: 17%

*average values for a representative of the group.

Recycled content

34%

Recyclability

- Recycling: 100%
- Downcycling: 0%

*average values for a representative of the group.

Packaging

Materials: cardboard + foil

Recyclability: 100%

Fabric technical data

M-62054 Mustard

| | |
|---------------------------------------|---|
| Material | 100% polyester |
| Weight | 364g/m2 • 510g/lm |
| Abrasion resistance rubs | 75,000 Martindale cycles; 100,000 double rubs wyzenbeek ASTM D4157 |
| Pilling resistance | scale 1-5, max 5 • EN ISO 12945-2 4 |
| Colour fastness to light | scale 1-8, max 8 • EN ISO 105 - B02 5-7 |
| Colour fastness to rubbing | scale 1-5, max 5 • EN ISO 105x12 (wet/dry) 4-5/4-5 |
| Acoustic test sound absorption | ISO 354 |
| Flammability | BS EN 1021 - 1:2006 (cigarette), BS EN 1021 - 2:2006 California Bulletin CAL 117-E-Class 1 |
| Fabric manufacturer's warranty | 10 years |